

9 PORT UNDERFLOOR POWER MDB 6mm²

9 circuit 9 port outlet boxes with 28 core 6.0mm² Home Run cables. The Home Run cable has a gland and locknut to fix to the Distribution Board header trunking and 3m tails for on site wiring. The length of the home run will vary dependant on its position within the building. The ## in the part number denotes the home run length in metres.



TECHNICAL SPECIFICATION

Number of Cores: 27 + E

Power Diameter: 27 x 6.0mm² L, N, E + 1 x 4.0mm² CPC

Rate current (A): 32 A (max)

Rate impulse voltage: 4 kV

Power Outputs: 3 Pin (9 Ports)

Rated Voltage: 250/400 V

Frequency (HZ): 50 Hz

Mechanical Coding: Code 1 (Blue)

Lockable: self-locking (unlocking by disconnect tool)

Degree of protection (IP): IP20 (disconnected), IP40 (connected)

Connector standard: IEC61535:2009+A1:2013

QMS: ISO9001:2016

Wiring and Test Standard:


BS8488:2009+A1:2010

Available Lengths:

10m, 15m, 20m, 25m, 30m, 35m

Part code and box references will be on the packaging, MDB, and cable drum.

9 PORT UNDERFLOOR POWER MDB 6mm²



Warning: This device should be installed by a Qualified Electrician in accordance with the latest edition of the IEE Wiring Regulations and any applicable building regulations.